

Komfire 75

Quick Sheet



Non-Fire Rated
Solid & Glazed
Partitioning

Think partitioning.
Think Komfort.

Komfire 75 is Komfort's framed solid and glazed partitioning system, constructed with single layered plasterboards and steel internal structure, using 6.4-6.8mm glass in single and double glazed configurations with a minimal aluminium trackwork with angular or square edges. The system is fully demountable and relocatable.

Overview	
Maximum Screen Height	4200mm*
Maximum Module Width	1200mm
Maximum Doorset Height	3000mm*
Trackwork Dimensions	96x35mm
Deflection Head	None
Acoustic Performance	Up to 48dB (R_w)*
Structural Performance	Up to Medium
Fire Performance	None

* Depending on configuration & specification



Solid



Glazed



Door Frame

Optional Extras & Finishes

✓ Blinds*	✓ Manifestations	✓ Graphics
✓ Komfort Doors (Sonik*, Glass, Timber)	✓ Switch Glass	✗ Curved Glass
✓ Polyester Powder Coat Finish	✗ Satin Anodised Finish	✓ Special Anodised Finish

* Depending on configuration & specification

Performance Summary	Acoustics	Max. Height Duty Ratings to BS 5234-2:1992			
Solid/Glazed Configuration	dB Rating	Light	Medium	Heavy	Severe
Solid with Single Layered 12.5mm Wallboard	43dB (R_w)	3600mm	2700mm	-	-
<i>Alternatively with Timber Stud Inserts</i>		4200mm	4200mm	-	-
Solid with Single Layered 12.5mm SoundBloc	48dB (R_w)	3600mm	2700mm	-	-
<i>Alternatively with Timber Stud Inserts</i>		4200mm	4200mm	-	-
Single Glazed with 6.4mm Laminated	35dB (R_w)	3000mm	2700mm	-	-
Single Glazed with 6.8mm Acoustic Laminated	36dB (R_w)	3000mm	2700mm	-	-
Double Glazed with 6.4mm & 6.4mm Laminated	40dB (R_w)	3000mm	2700mm	-	-
Double Glazed with 6.4mm & 6.8mm Acoustic Lam.	41dB (R_w)	3000mm	2700mm	-	-

For further information please refer to the Komfire 75 Design Guide or contact our Specification Team.



This product is available on **NBS Source**.



Not currently available for this product.



THE INTERNATIONAL EPD® SYSTEM
Not currently available for this product.

Birmingham Head Office
Tel | +44 (0) 121 332 2560
headoffice@komfort.co.uk

Specifier Support
Tel | +44 (0) 121 332 2550
specifiersupport@komfort.co.uk

Technical Support
Tel | +44 (0) 1403 390 390
technical@komfort.co.uk