

Kross Glaze 600 Quick Sheet



Kross Glaze 600 is Komfort's industrial style framed split glazing system with matching rebated acoustic door and can be configured as offset single or double glazed with 90-degree, 135-degree and three-way posts.

Overview	
Maximum Screen Height	3000mm
Maximum Module Width	1200mm
Maximum Doorset Height	3000mm
Trackwork Dimensions	54mm
Deflection Head	None
Acoustic Performance	Up to 41dB (<i>R</i> _w)*
Structural Performance	Up to Light Duty
Fire Performance	None









Double Glazed



Door & Frame

- Blinds
- Kross Glaze Doors
- ✓ Polyester Powder Coat Finish
- * Depending on configuration & specification

- ✓ Manifestations
- Switch Glass
- * Satin Anodised Finish
- ✓ Graphics
- Curved Glass
- Special Anodised Finish

For further information please refer to the Kross Glaze 600 Design Guide or contact our Specification Team.



This product is available on NBS Source.



Not currently available for this product.



THE INTERNATIONAL EPD® SYSTEM Not currently available for this product.

Birmingham Head Office Tel | +44 (0) 121 332 2560 headoffice@komfort.co.uk

Specifier Support Tel | +44 (0) 121 332 2550 specifiersupport@komfort.co.uk Technical Support Tel | +44 (0) 1403 390 390 technical@komfort.co.uk

Performance Summary Glazing Configuration **Duty Rating** Max.Height Single Glazed with 6.8mm Acoustic Laminated 34dB (Rw) 29dB (R_w) Light 3000mm Single Glazed with 10.8mm Acoustic Laminated 37dB (R_w) 30dB (R_w) Light 3000mm 38dB (*R*_w) Single Glazed with 12.8mm Acoustic Laminated 33dB (R_w) Light 3000mm Double Glazed with 6.4mm & 6.8mm Acoustic Lam. 41dB (R_w) 36dB (R_w) Light 3000mm